

Model : VP-IPC-IRD2200MP



2.0MP H.265+ Motorized Lens IR Dome IP Camera		
Model	VP-IPC-IRD2200MP	
Camera	Sensor	1/2.8" 2.0Mega progressive scan CMOS
	Min.illumination	Color 0.01Lux@F1.2 (AGC ON); 0Lux@F1.2 (AGC ON) with IR
	Lens	2.8-12mm Motorized Lens
	IR Range	Up to 30m
	Electronic Shutter	Auto (1/25s ~ 1/10000s)
	Day / Night	Auto / Color / B&W (IR CUT)
	DNR	2D/3D DNR (Auto / Manual)
	Anti-Fog	Support (ON/OFF)
	WDR	DWDR
	BLC	Support
	Image Adjustment	Sharpness, Brightness, Saturation, Contrast Adjustable
Encode	Video Encoding	H.265+, H.265 Main Profile/H.264 High Profile/H.264 Main Profile/H.264 BaseLine Profile
	Max Resolution	Main Stream : 1920*1080@25/30fps ; Sub Stream : 704*576@25/30fps
	Triple Stream	The Third Stream : 1280*720@25fps
	Video Bitrate Control	Support VBR / CBR
	Video Bitrate Range	32Kbps~8Mbps
	Audio Encode	G.711A/G.711Mu/G.726
	Audio Bitrate	G.711A (64Kbps) /G.711Mu (64Kbps) /G.726 (16Kbps)
	Reduce Echo	Support
	Noise Filtering	Support
	Other Audio Function	Support Automatic Gain Adjustment; Audio Input/Output Volume Adjustable
Interface	Audio	1 Audio Input, 1 Audio Output.
	Alarm	1 Alarm Input, 1 Alarm Output.
	Local Storage	Support Micro SD/SDHC/SDXC (128G)
	RS485	Support
	Reset	Build in Reset Button

	Analog Output	1ch BNC Analog Output
	Network Port	1 RJ45 10M/100M Ethernet interface
Function	Motion Detection	Multiple Detection Zones, Variable Sensitivity Levels
	Corridor Mode	Support
	ROI	Support
	Privacy Masking	4 Zones for Privacy Masking
	Snapshot	Support JPEG, Resolution is the max encoding resolution
	Security Features	Support password, watermarking
	Text Overlay	Support (Channel name, Date&Time)
	Alarm	Support network anomaly, mask alarm and etc.
	Intelligent Function	Face Detection, Intrusion Detection, Object Missing/Left Detection, Through Fence Detection, Retrograde Detection, Loitering Detection, Density Detection, Counting, Color Cast, Car License Detection, Out of Focus Detection, Camera Movement Detection.
	Mobile Phone APP	Support IOS and Andriod
	Network Protocol	TCP/IP ; UDP ; HTTP ; IGMP ; ICMP ; DHCP ; RTP/RTSP ; DNS ; DDNS ; FTP ; NTP ; PPPOE ; UPNP ; SMTP
	Protocol	ONVIF/CGI/GB28181
General Parameter	Protection Grade	IP67/IK10
	Power Supply	DC12V (±25%) / POE
	Working Temperature	-40°C-- +60°C (*Start up should be done at above -40°C)
	Humidity	10%--90%
	Power	8W MAX
	Install Type	Wall or Ceiling Installation, support quick mount base.
	Size	137.99 x 110 (mm)
	Weight	750g

